Project Specifications

General Notes

- ALL WORK SHALL BE IN CONFORMANCE WITH THE EXISTING LABOR LAWS, SAFETY REQUIREMENTS AND OTHER REGULATIONS, AS REQUIRED BY THE CITY, THE STATE OF WASHINGTON, THE FEDERAL GOVERNMENT AND THE OWNER. THE CONTRACTOR SHALL ASSUME SOLE AND COMPLETE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION, INCLUDING THE SAFETY OF ALL PERSONS AND PROPERTY. THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS.
- 2. ALL WORK AND MATERIAL SHALL MEET THE REQUIREMENTS OF THE APPLICABLE DETAILS SHOWN ON THE DRAWINGS, AND CONFORM TO THE CURRENT STANDARD SPECIFICATIONS FOR ROAD, BRIDGE AND MUNICIPAL CONSTRUCTION, AS ISSUED BY THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION (WSDOT). HEREAFTER SECTION NUMBERS REFER TO WIDOT SPECIFICATIONS UNLESS NOTED OTHERWISE.
- 3. ALSO INCORPORATED INTO THESE CONTRACT DOCUMENTS BY REFERENCE ARE:
 - a. MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS (MUTCD), CURRENT EDITION, WITH WSDOT MODIFICATIONS, IF ANY; b. CITY DEVELOPMENT GUIDELINES AND PUBLIC WORKS STANDARDS, CURRENT ADDITION, WHICH IS REQUIRED TO BE ON-SITE WITH APPROVED PLANS;
- 4. CONTRACTOR SHALL OBTAIN COPIES OF THESE PUBLICATIONS AT OWN EXPENSE AND 6. HAVE ACCESSIBLE ON-SITE AT ALL TIMES DURING CONSTRUCTION.
- 5. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING ALL LABOR, MATERIALS, TOOLS, FOUIPMENT, TRANSPORTATION, SUPPLIES, AND INCIDENTALS REQUIRED TO COMPLETE ALL WORK SHOWN ON THESE DRAWINGS AND TO OBTAIN ACCEPTANCE BY THE CITY AND THE PROJECT OWNER.
- 6. THE CONTRACTOR SHALL CONFORM TO LABOR AND INDUSTRIES REQUIREMENTS WITH REGARD TO SAFETY, CONFINED SPACE ENTRY, AND ALL OTHER APPLICABLE SECTIONS TO THIS PROJECT.
- 7. THE INTENT OF THESE DRAWINGS IS TO DESCRIBE A COMPLETE WORK. OMISSIONS FROM THE DRAWINGS OF DETAILS OF WORK WHICH ARE NECESSARY TO CARRY OUT THE INTENT OF THE DRAWINGS SHALL NOT RELIEVE THE CONTRACTOR FROM PERFORMING THE OMITTED WORK,
- 8. THE CONTRACTOR SHALL COORDINATE ALL CONSTRUCTION ACTIVITIES WITH ADJACENT PROPERTY OWNERS. DRIVEWAYS AND UTILITY SERVICES SHALL REMAIN ACCESSIBLE AT ALL TIMES.
- 9. CONTRACTOR SHALL NOTIFY AND COORDINATE WITH OTHER UTILITIES AS NEEDED FOR DURATION OF THE PROJECT.
- 10. A PROPOSED ALTERATION BY THE CONTRACTOR AFFECTING THE REQUIREMENTS AND 1. WHEN EXCAVATION ACTIVITIES EXPOSE PEAT, SOFT CLAY, QUICKSAND, DEBRIS, FORMATION IN THESE DRAWINGS SHALL BE IN WRITING AND WILL REQUIRE APPROVAL OF ENGINEER AND OWNER.
- 11. ALL CONNECTIONS TO WATER, SEWER, AND STORM DRAIN SYSTEMS, I.E., TIE-INS OR RELOCATIONS, WILL REQUIRE SHOP DRAWINGS PRIOR TO CONSTRUCTION.
- 12. ALL MATERIAL SUBMITTALS TO BE APPROVED PRIOR TO CONSTRUCTION INCLUDING SHOPS DRAWINGS, TRAFFIC CONTROL PLANS, SHUT DOWN NOTICES, AND FLUSHING
- 13. THE CONTRACTOR SHALL SUBMIT CATALOG DATA, CUT SHEETS, SHOP DRAWINGS AND Drainage OTHER INFORMATION TO THE ENGINEER AND THE OWNER FOR REVIEW OF MATERIALS AND CONSTRUCTION PROCEDURES FOR ALL MAJOR MATERIALS, APPURTENANCES, AND EQUIPMENT, MAJOR MATERIALS INCLUDE PIPE, DRAINAGE STRUCTURES, BACKFILL MATERIAL, CRUSHED SURFACING MATERIAL, CONCRETE AND ASPHALT.
- 14. ALL AREAS DISTURBED DURING CONSTRUCTION SHALL BE RESTORED TO THEIR DRIGINAL "PRE-CONSTRUCTION" STATE OR BETTER
- 15. CONTRACTOR TO PROVIDE SHORING MEETING THE REQUIREMENTS OF SECTION 7-08.3(1)B OF THE STANDARD SPECIFICATIONS.
- 16. A PRE-CONSTRUCTION MEETING IS REQUIRED AT LEAST TWO WEEKS PRIOR TO

Survey And Datum

36.0

TOPOGRAPHIC AND PROPERTY LINE INFORMATION DEPICTED HEREON WAS PROVIDED BY SURVEY, PROJECT DATUM IS NAVD88 VERTICAL AND NAD 83/91 HORIZONTAL.

Contractor As-built

- CONTRACTOR SHALL MAINTAIN ONE SET OF THE CONTRACT DRAWINGS THAT SHALL INCLUDE, CLEARLY AND LEGIBLY MARKED, ANY ALTERATION OR LOCATIONS OF UNDERGROUND UTILITIES ENCOUNTERED DURING PROGRESS OF THIS PROJECT, AND ANY ALTERATIONS MADE TO THE IMPROVEMENT BEING INSTALLED. SAID DRAWINGS PROJECT COMPLETION.
- 2. THE CONTRACTOR SHALL MAINTAIN REDLINES, FIELD NOTES AND DIGITAL PHOTOGRAPHS TO DOCUMENT ALL IMPROVEMENTS OR VARIATIONS AS WORK PROGRESSES. CONTRACTOR SHALL MAINTAIN DOCUMENTATION ONSITE AT ALL TIMES AND SHALL MAKE IT AVAILABLE FOR OWNER REVIEW. THE DOCUMENTATION SHALL BE PROVIDED TO THE OWNER IN AUTOCAD ELECTRONIC FORMAT AT THE COMPLETION OF CONSTRUCTION FOR USE IN PREPARATION OF RECORD DRAWINGS.

Utilities Location

APPROXIMATE LOCATIONS OF EXISTING UTILITIES HAVE BEEN OBTAINED FROM AVAILABLE RECORDS AND ARE SHOWN FOR CONVENIENCE. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING LITHLITIES. THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO CONSTRUCTION BY CALLING UNDERGROUND LOCATE LINE AT 811 A MINIMUM OF TWO FULL WORKING DAYS PRIOR TO BEGINNING ANY EXCAVATION, AND BY POTHOLING ALL EXISTING UTILITIES PRIOR TO CONSTRUCTION TO VERIFY DEPTH.

Work Within The Right-of-Way

1. CONTRACTOR SHALL OBTAIN A PERMIT PRIOR TO ANY WORK WITHIN THE CITY RIGHT-OF-WAY, ALL WORK WITHIN THE RIGHT-OF-WAY SHALL ADHERE TO CITY STANDARDS AS OUTLINED IN THE PERMIT. MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE CURRENT EDITION OF THE WSDOT STANDARD SPECIFICATIONS, CURRENT ADDITION OF MUTCD, AND CITY PUBLIC WORKS

Erosion Control

- ALL EROSION CONTROL MEASURES SHALL MEET THE REQUIREMENTS OF THE CITY
- 2. A TEMPORARY EROSION AND SEDIMENT CONTROL PLAN HAS BEEN PREPARED AND INCLUDED IN THE CONTRACT DRAWINGS.
- 3 FROSION CONTROL MEASURES ARE NOT LIMITED TO THE ITEMS ON THESE PLANS. THE CONTRACTOR IS RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ALL EROSION CONTROL MEASURES. NO SILTATION OF EXISTING OR PROPOSED DRAINAGE FACILITIES SHALL BE ALLOWED, CARE SHALL BE TAKEN TO PREVENT MIGRATION OF SILTS TO OFF-SITE PROPERTIES. ALL DISTURBED EARTH CAUSED BY CONTRACTOR'S ACTIVITIES SHALL BE HYDROSEEDED.
- ALL SEDIMENT CONTROL DEVICES INCLUDING, BUT NOT LIMITED TO, SEDIMENT PONDS PERIMETER SILT FENCING, OR OTHER SEDIMENT TRAPPING BEST MANAGEMENT PRACTICES, SHALL BE INSTALLED PRIOR TO ANY GROUND DISTURBING ACTIVITY.
- TEMPORARY OR FINAL STABILIZATION OF ALL EXPOSED AREAS SHALL BE WITHIN 48 HOURS AFTER REACHING FINISHED GRADE.
- AREAS OVER 5,000 SQUARE FEET TO BE PAVED MUST BE PROVIDED WITH A CRUSHED ROCK SUBBASE OR OTHER APPROVED ARMORING WITHIN A MINIMUM OF SEVEN (7) DAYS AFTER REACHING GRADE. EXPOSED SOILS REQUIRE TEMPORARY STABILIZATION IF UNWORKED FOR MORE THAN 2 DAYS DURING THE WET SEASON (OCTOBER 15TH TO MAY 30TH) OR MORE THAN 7 DAYS DURING THE DRY SEASON (JUNE 1ST TO SEPTEMBER 30TH).
- 7. THE CONTRACTOR SHALL REMOVE ALL TEMPORARY BMPS AND ALL ASSOCIATED HARDWARE FROM THE PROJECT LIMITS PRIOR TO PHYSICAL COMPLETION UNLESS OTHERWISE APPROVED BY THE ENGINEER.

Dewatering

1. FOUNDATIONS, UTILITY TRENCHES, AND ALL OTHER PARTS OF THE CONSTRUCTION SITE SHALL BE DEWATERED AND KEPT FREE OF STANDING WATER. AND MUDDY CONDITIONS AS NECESSARY FOR THE PROPER EXECUTION OF THE WORK. THE CONTRACTOR SHALL FURNISH, INSTALL, OPERATE, AND MAINTAIN ALL DRAINS, SUMPS, AND OTHER EQUIPMENT REQUIRED TO PROPERLY DEWATER THE SITE AS SPECIFIED. DEWATERING SYSTEMS THAT CAUSE A LOSS OF SOIL FINES FROM FOUNDATIONS AREAS WILL NOT BE PERMITTED. WATER SHALL BE DISCHARGED TO AN APPROVED LOCATION

Removal and Replacement of Unsuitable Materials

- OR OTHER UNSUITABLE FOUNDATION MATERIAL, SUCH MATERIAL SHALL BE REMOVED TO THE DEPTH DIRECTED BY ENGINEER AND BACKFILLED WITH SUITABLE APPROVED FOUNDATION MATERIAL
- 2. UNSUITABLE MATERIAL SHALL BE REMOVED FROM THE SITE AND HAULED TO AN APPROVED PERMITTED WASTE SITE OBTAINED BY THE CONTRACTOR. THE CONTRACTOR SHALL FURNISH AND PLACE SUITABLE MATERIALS MEETING THE REQUIREMENTS OF THE STANDARD SPECIFICATION.

1. SEE UTILITY DRAWING AND DETAILS FOR SPECIFICATIONS.

Excavation and Grading

- 1. THE CONTRACTOR SHALL DETERMINE THE TYPE OF EQUIPMENT AND METHOD TO USE TO ACHIEVE REQUIRED COMPACTION. THE CONTRACTOR SHALL ARRANGE FOR A GEOTECHNICAL ENGINEER TO TEST AND CERTIFY SOIL COMPACTION. THE OWNER SHALL RECEIVE COPIES OF ALL GEOTECHNICAL INSPECTION AND TEST REPORTS. EARTH COMPACTION SHALL BE CONSISTENT WITH STANDARD SPECIFICATIONS SECTION 2-03.3(14)C METHOD C.
- 2. THE PROJECT AREA SHALL BE EXCAVATED A MINIMUM OF 12-INCHES AND THE SUBGRADE COMPACTED IN PREPARATION FOR FINISHED SURFACES INCLUDING IMPORTED STRUCTURAL FILL PER THE GEOTECHNICAL REPORT A MINIMUM OF TWO MONTHS PRIOR TO BEGINNING CONSTRUCTION FOR BUILDING FOUNDATIONS.
- 3. PIPE BEDDING AND BACKFILL SHALL BE CSTC.
- 4. ALL AREAS OF FILL THAT WILL BE WITHIN THE BUILDING ENVELOPE SHALL BE COMPACTED IN ACCORDANCE WITH THE GEOTECHNICAL REPORT.
- HMA SHALL MEET THE REQUIREMENTS OF "HMA CLASS 1/2" PG 64-22" OF THE STANDARD SPECIFICATIONS, WITH 92% COMPACTION OF MAXIMUM DRY DENSITY
- 6. CSTC AND CSBC SHALL MEET THE REQUIREMENTS OF SECTION 9-03.9(3) OF THE STANDARD SPECIFICATIONS, WITH 95% COMPACTION OF MAXIMUM DRY DENSITY
- 7. THE PAVEMENT SECTION SHALL CONSIST OF THE FOLLOWING:

COURSE	THICKNESS (INCHES)	PERCENT COMPACTION
HOT MIXED ASPHALT	4	92
CSBC	12	95
PERCENT OF MAXIMUM D	DV DEHSITY (AST)	DIESTI

Abbreviations

VDJ	Adjust	MH	Manholo
AC ASPH	Asphalt Concrete Asphalt	MJ NAVD	Mechanical Joint North American Vertical Datum
ASSY	Assembly	(N)	North
AYE	Avenue	(NE)	Northeast
BC	Back of Curb	(NW)	Northwest
BFV	Butterfly Valve	NTS	Not to Scale
BLKG	Blocking	OD	Outside Diameter
BLDG	Building	O/S PC	Offset Point of Curvature
BVC	Bottom Begin Vertical Curve	PE	Professional Engineer
BVCE	Begin Vertical Curve Elevation	PERF	Perforated
BYCS	Begin Vertical Curve Station	PERM	Permanent
CARV	Combination Air Release Valve	PL	Property Line
CB	Catch Basin	PT	Point of Tangency
CDF	Control Density Fill	PVC	Polyvinyl Chloride
CI	Cast Iron Centerline	PVMT	Pavement Parking
CL	Class	PRV	Pressure Reducing Valvo
CMP	Corrugated Metal Pipe	PT	Point of Tangency
CO	Clean Out	PVI	Point of Vertical Intersection
CONC	Concrete	PVIE	Point of Vertical Intersection Elevation
CONST	Construction	PVIS	Point of Vertical Intersection Station
CONTR	Contractor	R	Radius
CPEP	Corrugated Polyethylene Pipe	RBC REO'D	Rebar and Gap Required
CPLG	Coupling Crushed Surfacing Base Course	RPBA	Reduced Pressure Backflow Assembly
CSTC	Crushed Surfacing Top Course	RT	Flight
DI	Ductile Iron	ROW	Right-of-Way
DIA	Diameter	S	Slope
DL	Daylight Earthwork	(S)	South
DS	Downspout	SDCB	Storm Drain Storm Drain Catch Basin
DWG	Drawing	SDMH	Storm Drain Calch Basin Storm Drain Manhole
(E)	Driveway East	SDR	Sidewall Dimension Ratio
EC	Erosion Control	(SE)	Southeast
EG	Existing Grade	SHT	Shoot
EGC	Existing Grade at Centerline	SS	Sanitary Sewer
ELEV	Elevation	SSCO	Sanitary Sewer Clean Out
EP	Edge of Pavement	SSMH	Sanitary Sewer Manhole
EVCE	End Vertical Curve End Vertical Curve Elevation	SST	Stainless Steel Street
EVCS	End Vertical Curve Station	STA	Station
EX	Existing	STD	Standard
FCA	Flange Coupling Adapter	STRUCT	Structure
FDC	Fire Department Connection	SW	Sidewalk
FG	Finish Grade	(SW)	Southwest
FGC	Finish Grade at Centerline	TC TELE	Top of Curb Telephone
FH FL	Fire Hydrant Flow Line	TEMP	Temporary
FLG	Flance	TESC	Temporary Erosion and Sediment Control
FND	Found	THRU	Through
FOC	Face of Curb	TP	Top of Pipe
GV	Gate Valve	TRANS	Transition
HDPE	High Density Polyethylene	TYP	Typical
HMA HORIZ	Hot Mix Asphalt	UNO	Unless Noted Otherwise Vertical
HYD	Horizontal Hydrant	VC	Vertical Curve
ILLUM	Illumination	VERT	Vertical
INV	Invert	W/	With
IE	Invert Elevation	(W)	West
INT	Intersection	WSE	Water Surface Elevation
IP	Iron Pipe		
JUNCT	Junction Left	SYMBOLS	
LF	Lineal Feet	O I MUOLO	
LS	Landscaped Surface	Δ	Delta
MAX	Maximum	#	Number
MD	Measure Down	&	And
MG/L	Milligrams per Liter	@	At

Sheet Index Sheet No. Drawing No. Sheet Title Notes, Legend, & Sheet Index C0.2 Existing Conditions & Bldg Setbacks Demolition & Eroslon Control C1.0 Demo & Frosion Control Plan C1,1 Demo & ESC Details C2.0 Site & Landscaping Plan C2.1 C2.2 Site Details C3.0 Water & Sewer Plan C3.1 Sewer Details 10 C3,2 Water Details 11 C3 3 Water Details Gradino & Storm Drainage C4.0 Grading & Storm Drainage Plan C4.1 Storm Drainage Details

Legends

Existing	Line Types	Existi	ng Symb
	Existing Building	¤	Existing Yard Light
	Existing Cable TV - Buried	Ω	Existing Hydrant
A	Existing Centerline Road	æ	Existing Water Me
	Existing Concrete, Curb,	M	Existing Gate Valv
	Gutter and Sidewalk	[W]	Existing Water Val
	Existing Creek/Ditch		Existing Mail Box
	Existing Fence	.u .	Existing Sign
	Existing Gas	M	Existing Conifer Tr
	Existing Guardrall	(3)	Existing Deciduou
	Existing Gravel	\sim	Existing Shrub
	Existing Pavement Edge	-0-	Existing Power Po
	Existing Power - Aerial	- 1	Existing Power Po
	Existing Power - Buried		Existing Power Tra
	Existing Right-Of-Way	P	Existing Power Va
	Existing Sanitary Sewer	0	Existing Sewer Cle
	Existing Storm Drain	0	Existing Sewer Ma
	Existing Telephone - Buried	>-<	Existing Storm Cu
	Existing Traffic Signal		Existing SDCB
	Existing Toe of Slope	0	Existing SDMH
	Existing Top of Slope	-0-	Existing Telephon
-CANARANANANANANANANANANANANANANANANANANA	Existing Brush Line	.1	Existing Telephon
	Existing Water	n T	Existing Telephon
	Existing Wetland Boundary	X	Existing Street Lig
	Existing Wetland Buffer	O	Existing Traffic Sig
4		Ø	Existing Junction I
Proposed Line	Types		Existing Gas Valve
	5 (8) 5 (1)	23	Existing Traffic Sig
	Proposed Storm Drain Line Proposed Water Line	D	and Cum
	Proposed Fire Line	Propo	sed Sym
	Proposed Sanitary Sewer Line	(0)	Proposed Storm D
	Proposed Gas Line	100	Proposed Catch B
	Proposed Diesel Line	0	Proposed Storm D
	Proposed Cable TV/Internet Lin	o A	Proposed Fire Hye
-1464464664664664646464646	Utility to be Removed/Abandone	nd HC	Proposed Gate Va

Proposed Silt Fencing

----- Proposed Say Cut Line

es	Existi	ng Symbols
	¤	Existing Yard Light
- Buried	A	Existing Hydrant
Road	EE	Existing Water Meter
Curb,	M	Existing Gate Valve
Sidewalk	[W]	Existing Water Vault
h		Existing Mail Box
	ъ,	Existing Sign
	A.	Existing Conifer Tree
	(:)	Existing Deciduous Tree
		Existing Shrub
Edge	-0-	Existing Power Pole
erial		Existing Power Pole Anchor
uried		Existing Power Transformer
Yay	P	Existing Power Vault
Sewer	0	Existing Sewer Cleanout
in	0	Existing Sewer Manhole
e - Buried	$\rightarrow \leftarrow$	Existing Storm Culvert
nal		Existing SDCB
pe	0	Existing SDMH
ре	-0-	Existing Telephone Pole
9	.1.	Existing Telephone Pole Anchor
	i i	Existing Telephone Riser
Boundary	★	Existing Street Light
Buffer	0	Existing Traffic Signal
	Ø	Existing Junction Box
		Existing Gas Valve
rain Line	(2 5)	Existing Traffic Signal Cabinet
ine	Propo	sed Symbols
9	60	Proposed Storm Drain Manhole
Sewer Line		Proposed Catch Basin
e		Proposed Catch Basin

	15.21	Existing traine digital exempt
)	ropo	sed Symbols
	0	Proposed Storm Drain Manhole
	100	Proposed Catch Basin
	0	Proposed Storm Drain Cleanout
	A	Proposed Fire Hydrant
	HC	Proposed Gate Valve MJ x FLG
	ж	Proposed Gate Valve MJ
	ᄯ	Proposed Fitting MJ
	卍	Proposed Fitting FLG
	ᅚ	Proposed Fitting MJ x FLG
	\triangleleft	Proposed Thrust Block
	\boxtimes	Proposed Double Check Detector
		Proposed Double Check Valve As
		Proposed Reduced Pressure Back

Proposed Water Meter

Survey Point

Proposed Sanltary Sewer Manhole

Proposed Sanitary Sewer Cleanout

SCHOOL R COLUMBIA COLLEGE ART BLDG AT BARNES SO 11 BARNES STREET KELSO, WASHINGTON LOWER (HEAD STAR 401 E NEW




GIBBS & OLSON

PERMIT SET 10-22-2018

NOTES, LEGEND, & SHEET INDEX

0366,0014 SHEET NO.

C0.1









LEGEND:

DEMOLITION

EXISTING TO BE REMOVED

EXISTING PIPE TO BE REMOVED AND DISPOSED/ABANDONED

---- SAWCUT LINE

EROSION CONTROL



RIPRAP CONSTRUCTION ENTRANCE



INLET PROTECTION

SILT FEN

DEMO & EROSION CONTROL CONSTRUCTION NOTES:

REMOVE & DISPOSE EXISTING ASPHALT PAVEMENT

REMOVE & DISPOSE EXISTING CONCRETE SIDEWALK

REMOVE & DISPOSE EXISTING CURB & GUTTER

REMOVE EXISTING FENCE BACKSTOP

5 REMOVE & DISPOSE EXISTING GRAVEL TRACK

6 REMOVE & DISPOSE EXISTING FENCE

7 REMOVE & REINSTALL EXISTING GOAL POST

INSTALL INLET PROTECTION, PER WSDOT STD PLAN 1-40.20-00, SHT C1.1

CONST TEMPORARY CONSTRUCTION ENTRANCE PER WSDOT STD PLAN I-80.10-02, SHT C1.1

(10) INSTALL SILT FENCE PER WSDOT STD PLAN I-30.15-02, SHT C1.1

PROTECT EXISTING UTILITIES/POLE/PEDESTAUFENCE

12) REINSTALL GRAVEL TRACK, MATCH TO EXIST TRACK

LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON





PERMIT SET 10-22-2018

DEMO & EROSION CONTROL PLAN

0366,0014 SHEET NO.

ILLI NO.

C1.0

ERBSION CONTROL GENERAL NOTES

- Y. ALL EROSION CONTROL DEVICES SHALL BE CONSTRUCTED IN ACCORDANCE WHILT THE EROSION CONTROL PLANANCEROSION CONTROL DETAILS AND IN PLACE PRICE TO SYART OF ANY LAND DISTURBING ACTIVITY.
- 2-ALLEROS(ONEREVENTION AND CONTROL/BMPS SHALÉ BEINSPECTED, MAINTAINEG AND REFERIED AS NEEDED THROUGHOUT CONSTRUCTION TO INSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION.
- E. PERFORM ATLACTIONS NECESSARY TO PREVENT FROSION AND CONTROL SEDIMENT; TRICTUDING DUST, FROM TEACHING THE CONSTRUCTION SITE.
- 4.AS CONSTRUCTION PROGRESSES AND SEASONAL CONDITIONS DICTATE, MORE EROSION AND SEMMENT CONTROLS MAY DESIREQUIRED TO ENSURE THAT SEDIMENT AND SEDIMENT LIDEN WAYERS DO NOT ENTER THE DRAINAGE SYSTEM, RONDWAYS, DR. SURFACE SVATERS.
- 5.5HFSTHAY AREREQUIRED TO HAVE A CERTIFIED EROSION AND SEDIMENT CONTROL (EAD) SHAYL KEEP A CURRENT HISPECTION LOG ONSTETHATS HALL BE AVAILABLE FOR CITY REVIEW.

STORM DRAIN GENERAL NOTES

LYOUT TAR. CT.1, PLOT DATE, 19/22/2018 SIGHTB PM, DRAWING SME DATE, 10/22/2018 4:09:44 PM, PLOTED BY. KNOGERS GIBBS & GLSON — DING TO PDF.PCJ, PLOT STICE TABLE: GIBBS—GLSON STANDARD MONOCHRONECTB, PAPER SIZE, ARCH FULL R

- 1. TRACER WIRESHALL BE INSTALLED IN THE SAME DRIENTATION TO THE INSTALLED NON-CONDUCTIVE PIPE INCONECONTINUOUS STRAND, INSTALLA WARNING TAPE 12/TO 18; INCHES ABOVETHE INSTALLEU PÎPE: CONTINUITY TESTÎNG OF TRÂCER WÎRE ÎS RECÎVÎNEU.
- 2: INSTALLED PIPE SHALL BE CLEANED BY USE OF HIGH PRESSURE NOZZLE AND VACUUM TRUCK PRIOR TO VIDEONIC OR TESTING.
- BEAVIDED THIS PECTION SHALL BE PERFORMED ON THE INSTALLED PIPE-VIDEO INSPECTION SHALL DEMONSTRATE NO DEFORMATION, MANUFACTURING OR INSTALLATION DEFECTS, OR ANY DEBRIS BY THE LINES, FOR APPROVAL AND ACCEPTANCE BY THE CITY.
- A. PRESSURE TESTING IN ALL STORM MAIN LINES IS REQUIRED.
- IS.IF SUBGRADE CONDITIONS ARE SUBSTANDARD, FOUNDATION MATERIAL SHARL/BEINSTALLED, YO THE DEPTH AS DIRECTED BY THE CITY ENGINEER.







LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON

LIMITS OF QUARRY SPALLS ~ (TYP.) BERN OR PARTIAL OR COMPLETE EXCAVATION

ISOMETRIC VIEW
STABILIZED CONSTRUCTION ENTRANCE STABLIZED CONSTRUCTION ENTRANCE SHALL MEET THE REQUIREMENTS

X = 1' - 0" FOR SLOPES 4H:1V OR FLATTER
X = 1' - 6" FOR SLOPES STEEPER THAN 4H:1 TYPICAL SECTION COMPOST BERM DETAIL

TEMPORARY SILT FENCE

PLACE GEOTEXTILE UNDER THE SPLLIVAY AND SIDE SLOPES, PROVIDE A CONTINUOUS LAYER BETWEEN THE GRAVEL/ROCK AND THE NATIVE EARTHEN MATERIAL TEMPORARY SEDIMENT TRAP

MISCELLANEOUS EROSION CONTROL DETAILS






G GIBBS & OLSON www.gibbs-olson.com 1157 3rd Avenue, Sulle 219 Longvlew, WA 98632 (360) 425-0991

DEMO & ESC DETAILS

PERMIT SET 10-22-2018

0366,0014 SHEET NO.

C1.1



22/2018 4:10:31 PM, PLOTTED BY: KROSERS SIZE: ARCH FULL BLEED D (36:00 X 24:00 II

S.DWG, LAYOUT TAB: C2.0, PLOT DATE: 10/22/2018 DWG TO PDF.PC3, PLOT STALE TABLE: GIBBS-OLSON











ASPHALT PAVEMENT



CONCRETE SIDEWALK



DETECTABLE WARNINGS



LANDSCAPING AREA





LIGHT POLE



CONST. HMA PARKING AREA w/ 4-IN HMA OVER 12-IN CSBC, OVER GRAVEL BORROW & GEOTEXTILE FOR SEPARATION, SEE DTL SHT C2.1





 \bigodot INSTALL (1) 11 FT x 19 FT ADA PARKING SPACE w/ 5 FT WIDE AISLE

5 INSTALL WHEEL STOP (TYP), SEE DTL SHT C2.1

6 INSTALL MUTCO SIGN R7-8

7 INSTALL STRIPING & PARKING SYMBOLS PER MUTCD

8 INSTALL CROSSWALK STRIPING PER MUTCO

9 INSTALL CONCRETE STANDARD STRAIGHT CURB. SEE DTL SHT C2.1

10 INSTALL DETECTABLE WARNING. SEE DTL SHT C2.1

INSTALL CURB & GUTTER TYPE A. SEE DTL SHT C2.1

TRENCH RESTORATION, SEE DTL SHT C2.1

install 4 FT Chain Link Fence, Type 4. SEE DTL SHT C2.2

CONNECT TO EXISTING FENCE

15) REINSTALL EXISTING GOAL POST, SEE SHT C1.0

INSTALL GRAVEL TRACK, MATCH TO EXIST, SEE SHT C1.0 FOR TRACK EXTENTS

PROVIDE 12-IN CURB CUT WITH 6-IN TAPERS & QUARRY SPALLS PAD, SEE DTL SHT C2.1

CONST THICKENED EDGE ON SOUTH SIDE OF SIDEWALK TO ACCOMMODATE SLOPE

STANDARD STALLS (9 FT x 19 FT) = 13

ADA STALLS (11 FT x 19 FT) = 1

PROPERTY AREA:

TOTAL PROPERTY AREA: 346,322 sf

NEW IMPROVEMENTS AREA: 31,260 s





GIBBS & OLSON www.glbbs-olson.com 1157 3rd Avenue, Sulle 219 Longvlow, WA 96632 (360) 425-0991

PERMIT SET 10-22-2018

SITE & LANDSCAPING PLAN

0366,0014 SHEET NO.

C2.0

LOWER COLUMBIA COLLEGE
NEW HEAD START BLDG AT BARNES (401 BARNES STREET
KELSO, WASHINGTON

SCHOOL

SITE DETAILS

0366.0014 SHEET NO.

GIBBS & OLSON
www.gibbs-olson.com
1157 3rd Avenue, Suite 219
Longview, WA 98532
(360) 425-0991

PRECAST CEMENT CONCRETE BUMPER CURB

4" 2 #3 BARS

SECTION DETAIL


2" CLEARANCE (TYP) ---

ATTACHMENT DETAIL

- 3:1 SAND & CEMENT GROUT 1" DEPTH

Wheel Stop Detail

4-INCH MIN COMP. DEPTH HMA CLASS ½", PG 64-22 12-INCH MIN, COMP. DEPTH CSBC, COMP. 95% OF MDD AS DETERMINED BY ASTM D1557 <\/<\ GEOTEXTILE FOR SEPARATION - SUBGRADE COMPACTED TO 92% OF MDD AS DETERMINED BY ASTM D1557 THICKNESS VARIES, SELECT
BORROW PER WSDOT 9-03.14(2),
COMPACTED 95% OF MDD AS
DETERMINED BY ASTM D1557 HOT MIX ASPHALT



CONCRETE SIDEWALK / PATIO




Pavement Sections N.T.s.


QUARRY SPALLS, 2 FT x 2 FT x 6-IN DEEP


6° CURB TAPER BIORETENTION PLANTER, SEE SHEET C4.0

Curb Cut Detail



PROMING TYCHI, JOYPROJECTS\QSGEOOT44GT\QARTRACT DRINING\QETAUS\VEXTUSDING, UNCUT TAB. C2.2, PLOT DATE. 19/22/2018 50444 PU, DRINING SWE DATE. 19/22/2018 40844 PU, DRINING SWE DATE. 19/22/2018 40844 PU DRINING SWE DATE. 10/22/2018 40844 PU DRINING SWE GATE TABLE. GBES-01SON STAUDARD MONOCHROLECTE PROFILE GBES-01SON STAUDARD MONOCHROLECTE









LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON





PERMIT SET 10-22-2018

SITE DETAILS

0366,0014 SHEET NO.

C2.2







Scale: (in Feet)

WATER

WATER LINE

FIRE LINE

MJ x MJ FITTING W/ THRUST BLOCK

SANITARY SEWER

LEGEND:

■ SANITARY SEWER LINE

CLEANOUT

WATER CONSTRUCTION NOTES:

- 1) INSTALL 1-IN WATER SERVICE CONNECTION PER CITY STD DTL W-010, SHT C3.1
- (2) INSTALL 11/2-IN POLYLINE 250 PSI RATING
- 3 CONNECT TO WATER LINE AT BLDG. SEE MECHANICAL DRAWINGS FOR CONTINUATION.
- 4-IN HOT TAP OF EXIST WATER MAIN PER CITY STD DTL W-260, SHT C3.2. INSTALL 4-IN GATE VALVE (MJxFL)
- 5 INSTALL 4-IN DI CL 52 FIRE LINE
- (6) INSTALL 4-IN DOUBLE CHECK VALVE DETECTOR ASSEMBLY W/ FOC PER CITY STD DTL W-360-K, SHT C3.2. CONNECT VAULT DRAIN TO STORM DRAIN.
- 7 INSTALL 4-IN 221/2° BEND (MJ) w/ THRUST BLOCK
- (B) INSTALL 4-IN 90° BEND (MJ) W/ THRUST BLOCK
- CONNECT TO FIRE SPRINKLER SYSTEM, SEE MECHANICAL DRAWINGS FOR CONTINUATION.
- (10) 6-IN HOT TAP OF EXIST WATER MAIN PER CITY STD DTL W-260, SHT C3.2. INSTALL 6-IN GATE VALVE (MJxFL)
- 11) INSTALL HYDRANT PER CITY STD DTL W-150, SHT C3.3

SEWER CONSTRUCTION NOTES:

- CONNECT TO EXISTING SANITARY SEWER MAIN W/ A SANITARY SEWER TAP PER CITY STD DTL SS-230, SHT C3.1
- (2) INSTALL 27 LF OF 6-IN SANITARY SEWER SERVICE LATERAL PER CITY STD DTL SS-150, SHT C3.1
- (3) INSTALL CLEANOUT PER CITY STD DTL SS-160, SHT C3.1
- (4) INSTALL 145 LF OF 4-IN PVC ASTM D3034 SANITARY SEWER SERVICE LATERAL @ S = 0.02 FIFT (MIN) AND CONNECT TO SEWER LINE AT BLOG. SEE MECHANICAL DWGS FOR CONTINUATION.

GENERAL CONSTRUCTION NOTES:

- CONTRACTOR SHALL COORDINATE THE PIPING CONNECTION POINTS WITH BUILDING SUPPLIER PRIOR TO BEGINNING PIPELINE CONSTRUCTION
- ALL DUCTILE IRON FIRE LINE PIPING, VALVES AND FITTING JOINTS SHALL BE MECHANIGALLY RESTRAINED IN ADDITION TO THRUST BLOCKING.

LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOI 401 BARNES STREET KELSO, WASHINGTON

PERMIT SET 10-22-2018

WATER & SEWER PLAN

0366,0014

SHEET NO.

C3.0

SE. CO



MARK DATE DESCRIPTION	()		18000		
	Soup, P.S	n) (c		
	Soui (ox	DE 400	7	•	
11 G I			a alloas	E 200 8632 0000	HGKOUP.COM



LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON

PERMIT SET 10-22-2018



DOWNING. TICKNIL 3D/PROJECTS(OZGEODIA/ACT)COMTRACT DRAWINGSYDETALIS/DETALI

GIBBS & OLSON www.glbbs-olson.com 1157 3rd Avenue, Sulte 219 Longvlow, WA 98532 (360) 425-0991

SEWER DETAILS

0366,0014

SHEET NO.

C3.1



LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON



DOWNING. TYCHIL STYPROJECTS/GOSGOOJ44CT/CONTRACT DRAWINGS/DETALS/DETALS/DIG. LANDIT THE. C3.2. PLOT DATE: 10/22/2018 5:06:15 PM, DRAWING SWE DATE: 10/22/2018 4:08:44 PM, PLOTTED BY: KROGERS PROJECT STANDING WONCHROWECTE, PAPER STE. ARCH FILL BY PROJECT STANDING WONCHROWECTE, PAPER STE. ARCH FILL BY



PERMIT SET 10-22-2018

WATER DETAILS

0366,0014 SHEET NO.

C3.2

WAS	CATE OF A STATE OF A S	950 12h AVE. SUITE 200 LONGVIEW, WA 59622 LONGVIEW, WA 69622 AVE. ALL@COLLINSARCHGROUP.COM
) HITECTI	950 12th AVE LONGVIEW, PHONE: 360

LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON





PERMIT SET 10-22-2018

WATER DETAILS

0366,0014 SHEET NO.

C3.3

DRWING THOM, 31) PROBECTS (ORGEOIT ACTIONREAT DRWINGS VETMLS) VETMLS DRYCE _ZARDS CAS ACTION STATE THALE GRES & OLSON STRAIN STATE THALE GRES & OLSON STRAIN OF CUS INFERML SOIS — ON USERS, PLOT DEVICE _ZARDS & OLSON FROX, PLOT STATE THALE; GRES—GLSON STRAINS DIADORIOMECTE, PAPER SIZE, ARCH FULL B

SAVE DATE: 10/22/2018 4:18:58 PM, ARCH FULL BLEED D (36:00 X 24:00







Scale: (in Feet)

LEGEND STORM DRAINAGE

STORM DRAIN LINE

DRAINAGE FLOW ARROW

OVERFLOW STANDPIPE

o_{DS}

GRADING - - GRADE BREAKLINE

EXISTING ELEVATION P 33.40 ——— PAVEMENT ELEVATION, SEE NOTE 4

TC 33,40 — TOP OF CURB ELEVATION -----24----- CONTOUR

STORM DRAINAGE CONSTRUCTION NOTES:

- (SI) INSTALL 60-IN FLAT TOP STORM DRAIN MANHOLE. SEE DIT. SHT C4.1. CONNECT TO EXISTING 36-IN STORM DRAIN LINE. CONTRACTOR TO CONFIRM EXIST IE'S PRIOR TO CONSTRUCTION.
 - RIM = 18.20 IE IN = 13.00± 36-IN (N)(EXIST) IE IN = 14.85 12-IN ADS N-12 (W)(P1) IE OUT = 13.00± 36-IN (S)(EXIST)
- (S2) INSTALL 12-IN NYLOPLAST DRAIN BASIN W/ DOME GRATE. SEE DTL SHT C4.1 OVERFLOW. = 18.08 IE IN = 15.00 4.1N PERF PIPE (W) IE OUT = 15.00 12-IN ADS N-12 (E)(P1)
- (S3) INSTALL STORMWATER BIORETENTION PLANTER W.
 4-IN PERFORATED UNDERDRAIN. SEE DTI. SHT C4.1
 L = 90 FT
 W = 4 FT
 BOT EL = 17.58
- (P1) INSTALL 15 LF 12-IN ADS N-12 (WT) PIPE, S=0.005 FT/FT

- GENERAL 15 LF 12-IN ADS N-12 (WT) PIPE, S=0.005 FT/FT

 GENERAL GRADING/DRAINAGE NOTES:

 1. A MINIMUM OF 2 MONTHS PRIOR TO BEGINNING CONSTRUCTION FOR BUILDING FOUNDATIONS, THE CONTRACTOR SHALL REMOVE THE UPPER 12-INCHES OF TOP-SOIL AND COMPACT THE EXPOSED SUBGRADE USING A LARGE, SMOOTH DRUM, NON VIBRATORY ROLLER, FOLLOWING PREPARATION OF THE SUBGRADE IMPORTED STRUCTURAL FILL SHALL BE PLACED IN LIFTS AND OSMACH SHALL BE ACCOMPLISHED PER THE GEOTECHNICAL ENGINEERING REPORT PREPARATION OF THE UPPER 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND GRUBBING OF THE EXISTING VEGETATION, DEEPER THAN 12-INCHES OF TOP-SOIL AND CLEARING AND COMPACT OF THE WORK SHALL INSTALL SHAPPY OF THE WORK SHAPPY OF THE STRUCTURAL THE SHAPPY OF THE SHAPPY

- 5. ALL PERVIOUS AREA SUBJECT TO CLEARING & GRADING SHALL HAVE AN E-IN THICK TOPSOIL LAYER ADDED PRIOR TO SEEDING AND ALL LANDSCAPED PLANTING AREAS SHALL HAVE A 2-IN THICK MULCHED LAYER OF ORGANIC MATERIAL ADDED PRIOR TO PLANTING PER WISDOE SWMMWM, BMP T5.13, VOLUME V, CHAPTER V.
- ALL ON-SITE TOP OF CURB ELEVATIONS ARE 0.50' HIGHER THAN PAVEMENT ELEVATION UNLESS NOTED.





0366,0014 SHEET NO.

C4.0


PERMIT SET 10-22-2018

GRADING & STORM DRAINAGE PLAN


NEW

SCHOOL

12" NYLOPLAST DRAIN BASIN WITH DOME GRATE OVERFLOW STANDPIPE FOR BIORETENTION PLANTER




 $\underbrace{\text{Overflow Standpipe}}_{\text{N.T.s.}}$



NOTES:

- SCARIFY SUBGRADE 3" MIN, BEFORE BIORETENTION SOIL INSTALLATION
- 2. COMPACT BSM TO 85% PER ASTM 1577

Bioretention Planter



Roof Drain Perforated Stubout Connection





LOWER COLUMBIA COLLEGE NEW HEAD START BLDG AT BARNES SCHOOL 401 BARNES STREET KELSO, WASHINGTON





PERMIT SET 10-22-2018

STORM DRAINAGE DETAILS

0366,0014

SHEET NO.

C4.1