

**Sign and Pavement Marking
General Construction Notes (cont.)**

Other Pavement Markings: Other pavement markings shall used may be installed with one of the following materials.

1. Liquid Hot Applied Thermoplastic - Section 9-34.3(1) of WSDOT standard specifications
2. Pre-formed Cold Applied Pre-formed Type - Section 9-34.3(3)of WSDOT standard specifications
3. Liquid Cold Applied Methyl Methacrylate - Section 9-34.3(4) of WSDOT standard specifications

Other pavement marking shall be installed using the appropriate plan of Section M of WSDOT's standard plans.


BARRICADES:

All barricades shall comply with 6F.63 of the MUTCD with the additions below.

Type III Barricades: Type III barricades shall be made of material that is considered breakable (plastic, ½ " plywood, 1"X 8" or 12" pine or fir). Type III Barricades used to close a street shall have both right and left stripes and be accompanied with either a road closed or end of roadway sign.

RAISED PAVEMENT MARKINGS:

All raised pavement markings shall conform with sections 8-09 and 9-21 of the WSDOT standard specifications.

	SIGNS & PAVEMENT MARKING - CONSTRUCTION NOTES	
	STANDARD PLAN: TR-076	CITY ENGINEER APPROVAL: Longview: C.B.
	DATE: FEB. 2008	Kelso: S.Z.